



同步精度	同步点数	产品型号	额定流量	输出压力	可用油量	电机功率	电机电压	操作类型	泵站外观
%FS	点		L/Min	MPa	L	kW	V		
1	4	SEPR1440W-4A	0.3X4	70	40	2.2	380	按钮或者触摸屏进行操作， 电磁阀执行相关动作指令。	
1	6	SEPR1460W-6A	0.3X6	70	60	3.0	380		
1	8	SEPR1460W-8A	0.3X8	70	60	4.0	380		
1	12	SEPR1480W-12A	0.3X12	70	80	5.5	380		
1	4	SEPR2460W-4A	0.9X4	70	60	5.5	380		
1	4	SEPR3460W-4A	1.5X4	70	60	11.0	380		
1	4	SEPR44100W-4A	2.1X4	70	100	11.0	380		
1	6	SEPR44120W-6A	2.1X6	70	120	18.5	380		
									

5	6	SEPR1460W-6C	0.60X6	70	60	7.5	380	按钮或者 触摸屏进 行操作，	
5	4	SEPR2460W-4C	0.90X4	70	60	7.5	380		
5	6	SEPR2480W-6C	0.95X6	60	80	11.0	380		
5	4	SEPR34100W-4C	1.45X4	60	100	11.0	380		
2	4	SEPR64120W-4B	3.8X4	21	120	7.5	380	电磁阀执 行相关动 作指令。	
2	6	SEPR64120W-6B	3.8X6	21	120	11.0	380		
2	8	SEPR64150W-8B	3.8X8	21	150	15.0	380		
2	4	SEPR94400W-4B	19.0X4	21	400	30.0	380		

备注：产品型号为 SEPR1440W-4A 的同步液压泵站为小型便携泵站外观。